

Utah Division of Air Quality New Source Review Section

Form 7 Condenser

Date		
Company	· · · · · · · · · · · · · · · · · · ·	
Site/Source		

Equipment Information							
1.	Provide diagram of condenser:		Manufacturer:				
			Model no.:				
3.	3. Heat exchange area (ft ³):						
Contaminant Inlet Conditions							
4. Name of contaminant:			5. Pollutant rate: Inlet:lbs/hr				
			Outlet:	lbs/hr			
	Average Operation		Maximum Operation				
6.	Coolant flow rate per cond Watergpm	denser: or Airscfm	Coolant flow rate per condenser: Watergpm or Airscfm				
	Other: Type	Flow rate	Other: Type	Flow rate			
7.	Gas flow rate:	scfm	12. Gas flow rate:	scfm			
8.	Coolant temperature: Inlet:°F Outlet:°F	9. Gas temperature: Inlet:°F Outlet:°F	13. Coolant temperature: Inlet:°F Outlet:°F	14. Gas temperature: Inlet:°F Outlet:°F			
10.	Efficiency of condenser:	%	15. Efficiency of condenser:	%			
Emissions Calculations (PTE)							
16. Calculated emissions for this device PM ₁₀ Lbs/hr Tons/yr NO _x Lbs/hr Tons/yr SO _x Lbs/hr Tons/yr VOCLbs/hr Tons/yr HAPsLbs/hr (speciate)Tons/yr (speciate) Submit calculations as an appendix.							

NOTE: 1. Submit this form in conjunction with Form 1 and Form 2.

2. Call the Division of Air Quality (DAQ) at **(801) 536-4000** if you have problems or questions in filling out this form. Ask to speak with a New Source Review engineer. We will be glad to help!

Instructions

- 1. Supply a diagram showing the features of the equipment.
- 2. Specify the manufacturer and model number of the equipment.
- 3. Supply the amount of heat exchange area in cubic feet.
- 4. List the contaminants found in the gas stream (use additional sheets if necessary).
- 5. Indicate how much pollutant is in the inlet and outlet gas stream in pounds per hour.
- 6. Indicate the coolant flow rate per condenser during normal operation. (List the fluid if not water or air)
- 7. Indicate the gas flow rate in standard cubic feet per minute during normal operation.
- 8. Supply the inlet and outlet coolant temperatures during normal operation.
- 9. Supply the inlet and outlet gas stream temperatures during normal operation.
- 10. Indicate the efficiency of the condenser during normal operation.
- 11. Indicate the coolant flow rate per condenser during maximum operation. (List the fluid if not water or air)
- 12. Indicate the gas flow rate in standard cubic feet per minute during maximum operation.
- 13. Supply the inlet and outlet coolant temperatures during maximum operation.
- 14. Supply the inlet and outlet gas stream temperatures during maximum operation..
- 15. Indicate the efficiency of the condenser during maximum operation.
- 16. Supply calculations for all criteria pollutants and HAPs. Use AP42 or Manufacturers data to complete your calculations.

f:\engineer\generic\2002 form revised 7/19/02